



Airhandlers (AH-N) DC Speed control

Compact stainless steel airhandlers

- Integrated 3-way valve for optimal temperature control
- Extremely quiet
- High performance boxblower with 0-10V speed control
- Multiple air outlets
- Stainless steel drainpan
- Return air filter

Airhandler package

The Clion-Marine Airhandler package consists of the following items: Airhandler unit, Control box, Display kit

Control box

Complete plug and play control box with prewired 1,2 metre cable loom, connectors and two temperature sensors (air/defrost sensor). The boards are electrical protected with automatic fuse with a manual reset on the outside of the box.

Display kit

Full color touch screen display compatible with Vimar bezels. The kit contains the following items: touch screen display, Vimar black bezel, RJ45 cable (10 metre)

Technical Specifications

	AH-N 18.0-26.0			AH-N 18.0-26.0 PLUS
Part number	CM0000113109			CM0000115817
Capacity (BTU/h)	18.000	24.000	26.000	18.000-26.000
Capacity (kW)	5,3	7,0	7,6	5,3-7,6
Voltage	220v/50/60Hz	220v/50/60Hz	220v/50/60Hz	220v/50/60Hz
Power consumption (A)	0,75	0,75	0,75	1,2
Weight (kg)	16,70	16,70	16,70	16,70
Airflow auto modus (m³/h)	400-1000	520-1000	620-1000	800-1400
Chilled water connection	3/4" / 19mm	3/4" / 19mm	3/4" / 19mm	3/4" / 19mm
Return air face area (cm²)	963	1.519	1.630	1.630
Supply air face area (cm²)	481	759	815	815
Hose connection (inch/cm)	2x7" / 178	2x7" / 178	2x7" / 178	2x7" / 178
Dimensions (LxWxH) (mm)	614*235*340	614*235*340	614*235*340	614*235*340
Cable length control box	1,20m	1,20m	1,20m	1,20m
Drain connection (mm)	12 (4x)	12 (4x)	12 (4x)	12 (4x)
Chilled waterflow (m³/h)	1	1	1	1

For complete operation an airhandler, control box and display kit are required!